

## Strong 733 L

<b>Manufacturing process</b>	Needlefelt		ISO 2424					
<b>Type of surface</b>	Flecked							
<b>Surface aspect</b>	Coarse Fibred		ISO 2424					
<b>Width</b>	200 cm		EN 984					
<b>Backing</b>	LV		ISO 2424					
<b>Fibre composition</b>	70% PP / 30% dorix® PA							
<b>Total fibre weight of use surface</b>	800 gr/m <sup>2</sup>							
<b>Total weight</b>	1000 gr/m <sup>2</sup>	+/- 15%	ISO 8543					
<b>Basis weight of pile</b>	1000 gr/m <sup>2</sup>	+/- 15%	EN 984					
<b>Total height</b>	5.0 mm	+15% / -10%	ISO 1765					
<b>Overall use class</b>	Commercial 33, Areas with heavy use		EN ISO 10874					
<b>Luxury class</b>	LC1		EN 1307					
<b>Castor chair suitability</b>	Yes, permanent use		EN 985					
<b>Stair suitability</b>	Yes, permanent use		EN 1307					
<b>Colour fastness to light</b>	≥ 5		ISO 105-B02					
<b>Colour fastness to rubbing, wet and dry</b>	≥ 4		ISO 105-X12					
<b>Colour fastness to water</b>	≥ 4		ISO 105-E01					
<b>Dimensional stability</b>	Shrinkage ≤ 1,2 %		ISO 2551					
	Extension ≤ 0,5 %		ISO 2551					
<b>Electrostatic charging</b>	< 2kV		ISO 6356					
<b>Vertical resistance</b>	≤ 1,0x10 <sup>8</sup> Ω		ISO 10965					
<b>Impact sound protection ΔLW</b>	20 dB		ISO 10140					
<b>Acoustical sound absorption αS</b>	<b>Hz</b>	125	250	500	1000	2000	4000	ISO 354
	<b>αW</b>	0,02	0,03	0,08	0,14	0,25	0,38	
<b>Evaluated sound absorptions grade αW</b>	0.15							ISO 11654
<b>Thermal resistance</b>	0.10 m <sup>2</sup> .K/W							ISO 8302
<b>Slip resistance</b>	DS (> 0,30)							EN 13893
<b>Flammability</b>	Cfl,s1 (Glued)							EN 13501-1
<b>Prodis-ID (GuT)</b>	2EFD887D							www.pro-dis.info
<b>Comments</b>	Construction principle: The cavity of the access floor generates an overpressure, which is pressing the air evenly through the carpet all over the area.							
<b>TÜV PROFICERT product</b>	Certificate number: 70 710 5617-3							

## Floorsymbols



## Certificates

